



Building Materials in Dredging , Maritime and Waterfront Construction

**Ir. Bernard Malherbe
Jan De Nul Group**



Maritime & Dredging 2010

2

Types of Infrastructures & Constructions


- Breakwaters
- Seadikes & Riverdikes
- Bank- & Reclamation confinement/revetment
- Reclaimations
- Quay-walls
- Locks
- Pumping culverts
- Berthing structures (dolphins,...)
- Sinkers
- Pipe – and cable-landfalls
- Beach & coastal protection structures






Port of IJmuiden (Nederland)

Construction method for breakwater extension: North & South Pier (1965)




Construction Stages of Rubble-Asphalt Breakwater



Construction Method of IJmuiden breakwaters



13. De twee belangrijkste concepties van de Combinatie IJmuiden: onderlossers en hefpontons met kraan, beide geadviseerd en in opdracht van Rijkswaterstaat ontworpen.



Maritime & Dredging 2010

To Pouloseur (naast Luik) staat een trein gereed voor vervoer van stenen naar IJmuiden.

Fitteropbouw van zilt naar groot materiaal.



Construction method of IJmuiden's breakwaters

Werksituatie van de kraanhefeilanden.

TRANSPORT OVER
HOGE DAM OP 4.50⁺



Jan De Nul
GROUP



Maritime & Dr

Port of Zeebrugge (Belgium)

1903-2003



Anno 1976



Anno 1990




Maritime & Dredging 2010

Anno 2003




Construction sequence of Zeebrugge breakwaters

1. De sleuf uitbaggeren met sleepzuiger of cutterzuiger




2. Grind storten op het geklepte zand




3. Zinkstukken afzinken




4. Bermen voor de bescherming van de damteien storten




5. De damkern opbouwen met T.V. of 1-3 ton




6. De 1-3 ton secondaire beschermlaag plaatsen





7. 25-30 ton betonblokken plaatsen



8. De kruin afwerken en eventueel zandoppervlak glad maken.



Engineering design of Zeebrugge Rubble-Mound Breakwaters on soft soil: soil- replacement and erosion protection



- Legende:**
- Geklept zand
 - Erosiegrind
 - Zinkstukken met steenballast
 - Bermen in breuksteen van 3 à 6 ton voor de zeewaartse kant en 1 à 3 ton voor de havenzijde
 - Filter tussen steen en zandopsputting
 - De damkern wordt met tout-venant gebouwd
 - De damkern wordt afgedekt met breuksteen van 1 à 3 ton
 - De zeewaartse kant van de dam wordt tegen golfaanval beschermd door het plaatsen van betonblokken van 25 tot 70 ton.



Dredging of soft soil-replacement trench & Construction of breakwater's core



Een zinkstuk op de zate.

Construction and placement of willow fascines for erosion protection of soft soil-replacement





Maritime 8

De positie van afzinkpontons, zinkstuk en steenstorter gedurende het afzinken.


Zeebrugge Port Extension: sequence of Rubble Mound Breakwater construction






Zeebrugge Port Extension: placement of 25t to 28 t concrete armour units of Rubble Mound Breakwaters

Melchorita Breakwater, PERU LNG (anno 2007)



Maritime & Dredging 2010
Wave-Flume Testing of Breakwater

First engineering rule in maritime construction: Terzaghi filter rules



Armouring Layer

Underlayer

Filterlayer (mineral or geotextile)

Geotextile:

- woven fabric
- Non-woven fabric
- Material: PP, HDPE,...




NET-GEWEVEN GEOTEXTIEL



GEWEVEN GEOTEXTIEL



GEWEVEN GEOTEXTIEL



Permeable but sand-tight construction:

$d_{15\text{upperlayer}} / d_{85\text{ underlayer}} < 5$ (bulk of underlayer cannot migrate trough pores of upperlayer)

$d_{50\text{ upperlayer}}/d_{50\text{ underlayer}} = 15 \dots 60$

$d_{15\text{upperlayer}} / d_{15\text{ underlayer}} = 5 \dots 40$


Layer thickness:

Filter-layer (e.g. gravel-sand): $> 0,10\text{m}$

Underlayer & Armour Layer: $3 \dots 5 \times d_{50}$


Gradation of Maritime Construction Materials

Figure 2
Gradation Limits for Quarry Material
Elevation Below -6.0/MLWS



UNIFIED SOIL CLASSIFICATION (ASTM D-2487-98)

MATERIAL TYPES	CRITERIA FOR ASSIGNING SOIL GROUP NAMES			GROUP SYMBOL	SOIL GROUP NAMES & LEGEND
	COARSE-GRAINED SOILS >50% RETAINED ON NO. 200 SIEVE				
COARSE-GRAINED SOILS >50% RETAINED ON NO. 200 SIEVE	GRAVELS >50% OF COARSE FRACTION RETAINED ON NO. 4. SIEVE	CLEAN GRAVELS <5% FINES	Cu>4 AND 1<Cc<3 Cu>4 AND 1>Cc>3	GW	WELL-GRADED GRAVEL
		GRAVELS WITH FINES >12% FINES	FINES CLASSIFY AS ML OR CL FINES CLASSIFY AS CL OR CH	GP	POORLY-GRADED GRAVEL
				GM	SILTY GRAVEL
	SANDS >50% OF COARSE FRACTION PASSES ON NO. 4. SIEVE	CLEAN SANDS <5% FINES	Cu>6 AND 1<Cc<3 Cu>6 AND 1>Cc>3	SW	WELL-GRADED SAND
		SANDS AND FINES >12% FINES	FINES CLASSIFY AS ML OR CL FINES CLASSIFY AS CL OR CH	SP	POORLY-GRADED SAND
				SM	SILTY SAND
FINE-GRAINED SOILS >50% PASSES NO. 200 SIEVE	SILTS AND CLAYS LIQUID LIMIT<50	INORGANIC	PI>7 AND PLOTS>"A" LINE	CL	LEAN CLAY
			PI=4 AND PLOTS<"A" LINE	ML	SILT
		ORGANIC	LL (oven dried)/LL (not dried)<0.75	OL	ORGANIC CLAY OR SILT
			PI PLOTS >"A" LINE	CH	FAT CLAY
	SILTS AND CLAYS LIQUID LIMIT>50	INORGANIC	PI PLOTS <"A" LINE	MH	ELASTIC SILT
			LL (oven dried)/LL (not dried)<0.75	OH	ORGANIC CLAY OR SILT
		ORGANIC		PT	PEAT



Determining parameters for:

• Non-cohesive grains:

- grain-size distribution
- volume-mass & specific density
- permeability

• Cohesive grains:

- water content (w) & Atterberg Limits (SL, PL, LL)
- Plasticity-Index : PI = LL – PL
(PI = high > Clay; PI = low > Silt)
- Liquidity Index: LI = (w-PL)/(LL-PL)
- Activity : A = PI / (% < 0,075mm)
(A < 0,75 Inactief; A 0,75-1,25: Normal; A > 1,25: Active)
- shear resistance, cohesion
- deformation properties (compressibility,...)
- permeability

A. Natural Building Materials

Clay

- **What is Clay ?**

For geologists, Clay is a fine-grained sediment, constituted of mainly alumino-silicate minerals (> 45 %), that are plate or flake-like grains with equivalent Stoke's diameters of 0,020 mm en 0,0001 mm.

For geotechnicians, Clays are soils constituted of particles with equivalent Stoke's diameters lesser than 0,002mm. Geotechnicians distinguish between under- normal or over-consolidated Clays, depending upon their consolidation degree as a function of their overburden history.



- **Typical geotechnical properties of Clays**

Low water-content : $w < 35 \%$

Low permeability : $k < 10^{-11} \text{ m/sec}$

High cohesion : $c_u = 10 \text{ tot } 150 \text{ kPa}$

Electronic microscope shots of Clay Minerals Illite & Kaolinite




Maritime & Dredging 2010

Clay as Building Material

- Domain of application of Clays

- Impermeable cores of dikes



- Impermeable revetment of water-retention dikes

- Colmatation layer of upland disposal facilities, ponds,...

- Workability of Clay depends upon

Plasticity


Natural water-content close to PL

Waterfront-dikes as water-retention structures: body of sand with clay-core

- Deltaplan (Netherlands)
- Sigma Plan (Belgium)



Waterfront Engineering :
Risks (of failure-induced damage) = Probability (of failure) x Damage (resulting from failure)



Ref after data contained in MKBA Rapport Sigma Plan, 2002

Mud



- **What is Mud ?**

Mud is a mixture-sediment : a mixture of fine sand,silt - particles (0,063mm to 0,002mm) and clay-minerals. Generally Mud has a high content in organic fractions (2 to 10 %) and CaCo_3 (till 35 %).

Mud is the typical sediment for estuaria, shallow seas and sheltered deposition areas. Mud has generally a high water-content. Mud is the building material for what will become Clay after consolidation.

Mud is a cohesive sediment with low shear-strength. Till recently, Mud was considered as inappropriate for recycling or re-use.

- **Geotechnical properties of Mud:**

High water- content : $w = 100 \text{ to } 250 \%$, , beyond LL

Medium to high cohesion: $c_u = 1 \text{ tot } 30 \text{ kPa}$

Flocculation (aggregation to larger particles, called Flocks)

Sand-admixture (co-precipitation in flocks)

Transition sediment between suspensions and soil: classic geotechnical laws do not apply...rheology is the science of stress-strain behaviour for such Non-Newtonian Fluids. Parameters influencing shear-strength: initial rigidity (yield stress) , dynamic viscosity and thixotropy (typical for Bingham fluids, a particular form of Non-Newtonian fluids)

After dewatering (accelerated consolidation by lagooning, sun-drying, filter-pressing, chemical dewatering,...), Mud can reach dry-volume-masses of 500 to 600 kgds/m³ (bulk-densities of order of 1,45 to 1,60).

Dewatered Mud can be re-used as an impermeable, cohesive, shapeable building-material with low-permeability: landscaping voor sight or sound-screen, fill-material with high deformation properties,.....


Gravitational dewatering by lagooning (load : 400 to 600 kgds/m²)

Mechanical dewatering by chamber filter-pressses.

Chemical dewatering by admixture of CaO (8 to 16 %): exothermic reaction (evaporation) and water-adsorption.



Day 1: just after filling the experimental lagoon with fresh Mud




Lagooning of Dredged mud, Ring-canal in Ghent, Belgium

**ENVISAN Grondverwerkingscentrum
Hulsdonk**




Day 36: Crust-drying with superficial cracks



Day 100: After crust-revolving

Decantation and Consolidation Properties of Mud



Sand

- What is Sand ?

Sand is typically a detrital sediment, constituted of individual particles and with a relatively low intergranular cohesion. The particles have equivalent Stoke's diameters of 0,063 mm to 2 mm.

Sand-grains are generally mono-mineral particles of Quartz (Si O_2), Feldspars (Al, Mg Si O_4) or of organic origin: these latter are generally coral-fragments, shell-fragments,...constituted of Calcite, Aragonite,(Ca Co_3).

- Geotechnical properties of sands are:

Low in-situ water-content : $w < 35 \%$

High permeability : $k > 10^{-6} \text{ m/sec}$

Subrounded or rounded grains of 0,063 mm to 2,0 mm

Sorting degree, d_{50} , d_{90} ,...of grain-size distribution

Compaction properties with generally a rapid compaction and a maximum compaction-density corresponding to a typical water-content (Proctor-density)

Angle of Internal Friction (varying between 27° and 40°), determining shear-strength, equilibrium inflow-slope, active/pассив soil stresses,...




Carbonate sand (Dubai)
 $d_{50} = 0,654 \text{ mm}$

Quartz sand (S Afrika)
 $d_{50} = 0,700\text{mm}$



Mar

Grain-size distribution of Carbonate Sand



Sand as Building Material

Sand is generally easy to excavate, to dredge, to transport and to reclaim (provided it is not too dilatant). Sand is also relatively cheap a building material, and depending upon reserves, hauling distances generally with prices within 4 to 15 €/m³.

Therefore is sand one of the most widely used building materials in waterfront and maritime engineering.

Applications are:

- **Bulk of dikes**
- **Beach-restaurations**
- **Land-reclamations**
- **Dike-reinforcements**
- **Aggregate for concrete**
- **Drainage-layers on disposal facilities**
- **Core of breakwaters**
- **Soil-substitution material**
-



One of the World's largest land-reclamations: Chek Lap Kok airport in Hong Kong (1982)

Hydraulic fill of dredged sand and accelerated consolidation with vertical drains



Land-reclamation at Pulau Tekong, Singapore (740 Mm³, 1999)



Maritime & Dredging 2010

32



Reclamation of Western Port Area at Zeebrugge (Belgium) for Flanders Container Terminal, FCT



Maritime & Dredging 2010

33

Compaction of hydraulic sand-fills



Rapid Impact Compaction (RIC),
at Ras Laffan Port, Qatar


Compaction typical results

VEE

100

Compaction degree of reclaimed and dumped sand

A. Layout



B. Compaction degree

normal values relative density in reclaimed and dumped sand
reclaiming above waterlevel : Dr 50%-60% ϕ : 37.5%-40%
dumping below waterlevel : D 40%-50% ϕ : 35%-37.5%
reclaiming below waterlevel : D 15%-35% ϕ : 27.5%-35%





Table 1. According to Schmertzmann(1978) , Villet and Mitchell (1981)

Classic Beach Replenishment: reclaiming supratidal beach at Cancún, Mexico




Sand as building material for Coastal Protection: Profile Nourishment and Feeder Berm for “soft” coastal protection at De Haan, Belgium



Dumping Feeder Berm



**De Haan Coastal Protection Works:
a major pioneering achievement.
Less than 5 % losses per year
during the first 10 years.**



Gravel

- **What is Gravel ?**

Gravel is a detrital sediment, constituted of individual particles with almost no intergranular cohesion. Particles have typically equivalent Stoke's diameters between 2 and 64 mm.

Gravel-particles are either mono-mineral particles like Silex (Si O_2), either rock-fragments of Limestone, Granite, Basalt,...

Gravel can also be fabricated by crushing rock

- **Geotechnical properties and determining parameters of gravel are:**

Specific volume-mass: between 2600 and 2800 kg/m³

Grain-shape and form

Sorting-degree of grain-size distribution

Abrasivity

Gravel as Building Material

- Filterlayer between sand and rubble-mound rock-layers
- Ballast material in caissons
- Protection-layer of geotextiles
- Bedding and blinding layer under concrete blocks, caissons,... (quay-walls)
- Back-wedge of gravity quay-walls to decrease active soil pressure
- Bank-revetment
- Ballasting of fascine-matrasses
- Backfill of pipeline/cable trenches
- Erosion-protection at toe of structures
- Gravel-columns for consolidation of low-bearing capacity soils
- Soil-substitution material
-



Rocks



What is Rock ?

Rock is either an assemblage of crystallized minerals (Igneous and Metamorphic Rocks) or of sediment-particles (Sedimentary rocks) or the result of massive bio-chemical precipitation of specific minerals ((Limestones,...)). Rock for waterfront/maritime engineering is produced in quarries, according to specific criteria of grading.

Rock is produced by blasting, break-hammering or cutting geologic rock-formations and grades run from 'Quarry-run' (the rest-product of quarry) to Underlayer Rock and Armour Rock, till individual rock-weights of approx. 10ton.

Rocks to be used in waterfront-engineering such as rubble-mound breakwaters must comply to a number of criteria, such as:

- homogeneity of rock-formation
- high specific density (> 2.400 kg/m³)
- limited internal faulting
- limited abrasivity and brittleness,...

Rocks that generally fulfill these criteria are massive Limestones, Granites, Diorites, Quartzite,....

Rocks that often exhibit brittleness are: Basalt, Gabbro,...

Rocks that often exhibit abrasivity ~~Marl, Chert, Lime, Sandstone...~~

Advantages of Natural Rock in Waterfront engineering are numerous:

- **Easy to install:** smaller fraction can be placed in bulk, coarser fraction (> 1 ton) with standard heavy-duty crawler cranes, hydraulic excavators,...
- **Easy to maintain**
- **Flexibele adaptative to subsoil settlements or irregularities**
- **Extremely sustainable for limestones, granites,...** provided a number of rock-mechanic characteristics-criteria are fulfilled
- **Manageable prices** (between 40 tot 100 €/ton: quarried, transported and installed)
- **Wide range of grades:**
 - **Fine grades:** 30/60 mm, 40/100 mm, 50/150 mm, 90/200 mm
 - **Medium grades:** 5/40 kg, 10/60 kg, 40/200 kg , 60/300 kg
 - **Coarse grades:** 300/1.000 kg, 1.000/3.000 kg, 3.000/6.000 kg, 6.000/10.000 kg



Granite Quarry, Seychelles



Maritime & Dredging 2010

Limestone quarry at Al-Kabra, Saudi Arabia



Jumbo-Drilling of drill-holes


Quarry operations for producing rocks



Loading & transport of blasted rocks



Bulk- placement of breakwater-core, Dubai, UAE



Determining Parameters of Rocks:

- Color: for aesthetic or environmental reasons (visual-impact, landscape-integration,...)
- Specific Density :
 - Oven-dry density ρ_d (in kg/m³)
 - Density after water-absorption (in kg/m³)
- waterabsorption: $W_{ab} = 100 \times \text{Mass of water absorbed/Dry Mass}(\%)$
- intrinsic porosity : $\text{Por} = \text{ca. } W_{ab} \times \rho_d$
- weathering degree
- homogeneity: internal faulting, layering, veins (Quartz,...),...
- compression strength UCS (Uniaxial Compression Strength in MPa)
- tensile strength
- accoustic properties V_{acc} (m/sec):
- abrasion-resistance: inter-rock abrasivity (Micro-Deval test)
- resistance to frost/thaw cycli
- drop-test resistance
- bulk porosity of rock-layer :
 - quarry – Run : 33 %
 - Filter-Layer (5 – 60 kg): 39 %
 - Underlayer (60 kg – 1000 kg): 38 %
 - Armour Layer (1000 kg – 10 t): 36 %

Loss in rock between Quarry weighing-bridge and final placement in breakwater.

(Losses are due to intermediate stockpilings, settlements, losses during placement,...)

Layer	Grade	Theoretical layer-thickness [m]	Percentage of losses %	Practical layer-Thickness [m]	Total losses integrated, incl placement
					Losses of stockpile, transport & settlement
Core (Quarry-Run)		≥ 1m	5%		2,14
Filter-Layer	5 – 40 kg	0,40	10%	0,44	2,15
Filter-Layer	10 – 60 kg	0,50	10%	0,55	2,15
Under-Layer	60 – 300 kg	0,80	10%	0,88	2,18
Under-Layer	0.3 - 1.0 ton	1,25	10%	1,38	2,18
Armour-Layer	1 - 3 ton	1,80	15%	2,07	2,20
Armour-Layer	3 - 6 ton	2,40	15%	2,76	2,20
Armour-Layer	6 - 10 ton	2,90	15%	3,34	2,20

Rock: some indicative parameter-values

Parameter	Unit	Sandstone	Limestone	Granite	Gabbro	Porphyre
Density	Kg/m3	2200-2600	2700 -2900	2600-2800	2800-3000	2550 -2800
Waterabsorption	%	4,0 – 8,0	0,5 - 3	< 0,5	< 0,2	< 0,5
Compression strength UCS	MPa	20- 80	60 -200	80 - 300	100-400	200-500
Tensile strength	MPa	2-4	2 - 5	2-4	1 - 2	1-2
Sonic velocity	m/sec	4.000	5.000	7.000	8.000	7.500

Location	Quarry run, Filter-Layer		Under-Layer & Armour - Layer, (Wem > 300 kg)		
	Wem< 300 kg	Wem > 300 kg	Absolute tolerance	Average tolerance	
	[m]	[m]			
Above water	0.20	0.40	0.35 * Dn50	0.30 * Dn50	
	-0.20	-0.20	-0.30 * Dn50	-0.25 * Dn50	
From 0 tot – 5m	0.50	0.80	0.60 * Dn50	0.50 * Dn50	
	-0.30	-0.30	-0.50 * Dn50	-0.40 * Dn50	
From – 5 tot -15 m	0.50	1.20 -0.40		0.60 * Dn50	
More than -15 m	-0.50	1.50 -0.50		-0.50 * Dn50	

Tolerances for Rocks used in Breakwaters

Wem = arithmetic average weight

(the total weight of a sample of one grade, divided by the number of stones)

W50 = mediane weight of one grade

(50% > / 50%<)

Exchange factors between W50 and Wem

Rock-grade	W50	Factor	Wem
	[kg]		[kg]
10 – 60 kg	35	1,30	27
60 – 300 kg	180	1,15	157
0,3 - 1,0 ton	650	1,10	591
1 - 3 ton	2.000	1,05	1.905
> 3 ton		1,00	

Exchange factors from d50 to dn50

Rock-grade	D50	Factor	Dn50
	[m]		[m]
10 – 60 kg	0,28	0,84	0,24
60 – 300 kg	0,48	0,84	0,41
0,3 - 1,0 ton	0,74	0,84	0,63
1 - 3 ton	1,08	0,84	0,91
3 - 6 ton	1,41	0,84	1,19
6 - 10 ton	1,71	0,84	1,45

dn50 = nominal rock-diameter for perfect spheric rock
 $(= \{ W_{50} / \rho_s \})^{0,333}$

d50 = average real irregular stone diameter
 $(= \{ W_{50} / (\rho_s / 0,60) \})^{0,333}$

d 50 = dn50 / 0,84


Examples of typical dimensions and weights of Rocks in Breakwaters

Layer	Grade	W 50	ρ_s	Rock volume	D 50
		[ton]	[ton/m³]	[m³]	[m]
Filter-Layer	5 – 40 kg	0,023	2,650	0,008	0,242
Filter- Layer	10 – 60 kg	0,035	2,650	0,013	0,280
Under-Layer	60 – 300 kg	0,180	2,650	0,068	0,484
Under-Layer	0.3 - 1.0 ton	0,650	2,650	0,245	0,742
Armour - Layer	1 - 3 ton	2,000	2,650	0,755	1,079
Armour- Layer	3 - 6 ton	4,500	2,650	1,698	1,415
Armour - Layer	6 – 10 ton	8,000	2,650	3,019	1,714

$$D_{50} = \left(\frac{W_{50}}{\rho_s} \cdot \frac{0.6}{0.6} \right)^{1/3}$$

Form-factor = 0,60

Rock Armour units: relationship between Rock Diameter and Rock Weight




Narrow grading		Wide grading		Very wide grading	
$D_{95}/D_{15} < 1.5$		$1.5 < D_{95}/D_{15} < 2.5$		$D_{95}/D_{15} > 2.5$	
Class	D_{95}/D_{15}	Class	D_{95}/D_{15}	Class	D_{95}/D_{15}
15-20 t	1.1	1-10 t	2.0	10-1000 kg	4.5
10-15 t *	1.1	1-6 t	1.8	10-500 kg	3.5
6-10 t *	1.2	100-1000 kg	2.0	10-300 kg	3.0
3-6 t *	1.3	10-60 kg *	1.8		
1-3 t *	1.4				
0.3-1 t *	1.5				

Table 5.17 Examples of heavy and light gradings

Note:

The gradings indicated with * are standard gradings in accordance with EN 13383 (see Section 3.4.3).


Rock supply works for breakwaters



Breakwater construction using earth-moving equipment and geotextiles




Singapore: Reclamation of Pulau Ubin and Pulau Tekong Islands



Key Figures:

Client : Housing and Development Board
Surface of land to create : 1.480 ha
Volume of Sand to reclaim: 164 Mm³
Length of Breakwater : 14.800 m'
Period: 2000 – 2005
Investment : 850 M €




Area A- at Pulau Tekong Kechil, June 2002

Singapore: Reclamation of Pulau Ubin and Pulau Tekong Islands

Design Elements:


- Storm Surge level: CD + 3m
- Natural waterdepths: CD- 2 to -20m
- Design Wave Height: $H_s = 0,6 \text{ m}$
- Design Wave Period : $T_m = 2,9 \text{ sec}$
- $V_{curr} = 1,5 \text{ m/sec}$



Dredging of soil-substitution trench: sandkey



Singapore, Pulau Ubin and Pulau Tekong Reclamation and Rock-Works



Karimun,(Ind) Quarry of Granitic Rock



Maritime & Dredging 2010

62

Sieving, grading, crushing of rock : dressing of the various grades



Maritime & Dredging 2010


63

Drop-test of Armour RAU on Underlayer, laying on geotextile



Pulau Ubin : Pulau Tekong: Method Statement

- Sand slope trimming



- Crane barge is used to carry out the sand slope preparation (cut and fill) below water level, while land-based excavator carries out the sand slope preparation above water level.
- Excess sand below $\pm 0.0m$ CD is loaded to a coaming barge or hopper barge and is used for the next area.
- Excess sand above $\pm 0.0m$ CD is loaded to a tipper lorry and is used for the next area.

Trimming of Sand-slopes






Maritime & Dredging 2010

Pulau Ubin/ Pulau Tekong: Method Statement

- Geofabric laying



- Class B & C material is stockpiled near the working area for both land and marine prior to placement of the fabric.
- Survey pegs at the crest line and at the slope down to the lowest water level are used as guides for the alignment of fabric during placement.
- Geo-fabric on roll is positioned at the crest (+4.53mCD) and unrolled down the slope to the water level with the aid of an excavator to control and maintain the proper alignment.



Maritime & Dredging 2010

69



Maritime & Dredging 2010

70



Maritime & Dredging 2010



Maritime & Dredging 2010




Maritime & Dredging 2010

73

Pulau Ubin/Pulau Tekong: Method Statement

- Armour Stone Placement



- Upon successful inspection of the class 'B' profile, the placement of armour stones follows.
- For the lower part of the slope or below water level, armour stones are placed to the designed levels by a floating crane barge or by the hydraulic excavator on the pontoon starting from the bottom.
- Above ± 0.00m CD, each armour stone is placed / pitched tightly⁷⁴ and accurately to the lines, levels and slopes as shown on the



Maritime & Dredging 2010

75



Maritime & Dredging 2010



Maritime & Dredging 2010

77



Maritime & Dredging 2010

78



Maritime & Dredging 2010



Maritime & Dredging 2010

80






Maritime & Dredging 2010

82

- Cement mortar placement

Pulau Ubin/Pulau Tekong: Method Statement



- Upon the success of armour stone profile inspection, and once the expected sand bund settlement was obtained, gaps between armouring stones from elevation +1.5mCD shall be filled up by cement mortar.
- Cement mortar shall be mixed on site and suitable concrete pump shall be used for placement.




Maritime & Dredging 2010



Maritime & Dredging 2010

85

Singapore: Reclamation of Pulau Ubin and Pulau Tekong Islands



Singapore, Pulau Ubin and Pulau Tekong Reclamation and Rock-Works (2000-2005)

Volume

- Dredging of sandkey trenches and filling with sand (dredging depth -20 mCD to -60 mCD): 20,400,000 m³
- Construction of sand bunds including vibroflotation: 23,700,000 m³
- Infilling of reclamation area with dredged clay: 15,000,000 m³
- Filling on top of the marine clay with sand: 150,000,000 m³
- Installation of geofabric: 1,000,000 m²
- Construction of sloping rock revetment: 1,000,000 m³
- Installation of Prefabricated Vertical Drains: 80,000,000 m
- Installation of a sheet pile wall serving as a silt curtain: 8.5km
- Installation and management of a staging ground receiving excavated good earth and soft clay from trucks for barging to Pulau Tekong: 6,300,000 m³ GE / 10,500,000 m³ SC
- Construction of a white sandy beach: 700,000 m³
- Dredging of access channels, including rock blasting: 3,000,000 m³
- Marine installation of gravel compaction piles: 74,000 m³
- Installation of silt curtains with floaters: 6 km



Palm Jebel Ali, Dubai Construction Phases

Maritime & Dredging 2010

88

Dykes,
Breakwaters
and
Coastal
Defence



19th JUNE 2004



10th OCTOBER 2004



Palm Jebel Ali Construction Phases


& Dredging 2010



**Landfill works with
THSD's 'Juan Sebastian
de Elcano'**




CRESCENT ISLAND : TYPICAL SECTION
PHASE 1



PALM ISLAND 2
CRESCENT ISLAND
TYPICAL SECTION
 SCALE : 1/400
PLAN 1 of 10




CRESCENT ISLAND : TYPICAL SECTION
PHASE 2



PALM ISLAND 2
CRESCENT ISLAND
TYPICAL SECTION
 SCALE = 1:400
PLAN = 3 of 10




CRESCENT ISLAND : TYPICAL SECTION
PHASE 3




PALM ISLAND 2
CRESCENT ISLAND
TYPICAL SECTION
 SCALE : 1:400
PLAN : 2 of 10

Dykes, Breakwaters and Coastal Defence



DJN


CRESCENT ISLAND : TYPICAL SECTION
PHASE 5



PALM ISLAND 2,
CRESCENT ISLAND
TYPICAL SECTION
 SCALE : 1:1400
PLAN : 5 of 10

DJN


CRESCENT ISLAND : TYPICAL SECTION
PHASE 6



PALM ISLAND 2
CRESCENT ISLAND
TYPICAL SECTION
SCALE : 1:1400
PLAN : 6M X 10M

DJN


CRESCENT ISLAND : TYPICAL SECTION
PHASE 7



PALM ISLAND 2
CRESCENT ISLAND
TYPICAL SECTION
SCALE : 1:400
PLAN : 7 of 10

DJN


CRESCENT ISLAND : TYPICAL SECTION
PHASE 8



PALM ISLAND 2
CRESCENT ISLAND
TYPICAL SECTION
 SCALE : 1:1400
PLAN : 8 of 10

DJN


CRESCENT ISLAND : TYPICAL SECTION
PHASE 9



PALM ISLAND 2
CRESCENT ISLAND
TYPICAL SECTION
SCALE : 1:1400
PLAN : 1:6000

DJN

CRESCENT ISLAND : TYPICAL SECTION
PHASE 10



PALM ISLAND 2
CRESCENT ISLAND
TYPICAL SECTION
SCALE : 1:1400
PLAN : 10 of 10

New Island Development (NID)

Scope

**Reclamation and construction of
underwater revetment berm**

Soil

Sand and calcarenite

Volume

Dredging: 29 million m³

Reclamation: 29 million m³

Dredging depth


**Borrow area depths between 25 and 30
metres**

Other works


Rock dumping: 3 million m³





New Island Development: Layout




Engineering of Submerged “Reef” Breakwater



Submerged Shield Breakwater (New Island, Dubai)



NID: Visualisation of Roundhead Structures



New Island Development (NID)


Equipment

- TSHD Juan Sebastian De Elcano and Gerardus Mercator
- CSD J.F.J. De Nul
- 2 split barges
- SSDV Pompei
- Positioning pontoon DN 121
- Rock transport barges DN 114, DN 115 and DN 116
- Split barge Verrazzano




Maritime & Dredging 2010


1




2




3




4



5



6








Maritime & Dredging 2010




Maritime & Dredging 2010


7



8



9









Maritime & Dredging 2010










NID in September 2008 (under construction)




Maritime & Dredging 2010

120


10



11




12









13




14




15




16



17




18




125



21



22



New Island Development: June 2009



Errors in rubble-Mound Breakwaters NOT to make !









Maritime & Dredging 2010

Comparison of Rock Armour Units (dens = 2.650 kg/m³) vs
Concrete Armour Units (dens = 2.400 kg/m³) cfr Hudson's formula




Armouring of Breakwaters with Concrete Armour Units, CAU's



ANTIFER CUBE




Xbloc




$$W = \frac{w_r H^3}{K_o (S_r - 1)^3 \cot \theta}$$


TETRAPOD



ACCROPODE®




DOLOS



HARO


CORE-LOC™



Type of Armour Block	TETRAPOD	ANTIFER CUBE	HARO	ACCROPODE ®	CORE-LOC™
Number of Layers	2	2	2	1	1
Armour Slope H/V	3/2	3/2	3/2	4/3	4/3
Porosity %	50	45	51 - 53	52	60
Breaking Waves Kd	7*	9*	13,8	12	16
% Damage	5	5	0,5	0	0
Concrete Volume per m ² of Slope	0.35 Hs	0.38 Hs	0.27 Hs	0.2 Hs	0.18 Hs
Relative Quantity of Concrete	1.9	2.0	1.3	1.0	0.9

CAU's

Type	Layers	History	Void Percentage	Concrete percentage
Antifer Cube	2	Developed in 1972 Sogreah (Fr)	45%	55%
Tetrapod	2	Developed in 1950 Sogreah	50%	50%
Dolos	2	Developed in 1970 (SA)	60%	40%
Accropode I	1	Developed in 1980 Sogreah	50%	50%
Accropode II	1	Developed in 1994 Sogreah	55%	45 %
Core-Loc	1	Developed in 2000 USACE & commercialised by Sogreah	60%	40%
Xbloc	1	Developed in 2004 DMC (NL)	60%	40%



Placement-rythms of CAU's in Breakwaters

cyclus time for different CAU's:

Type	2,50 m3, 6 ton		5,00 m3, 12 ton		10,00 m3, 24 ton	
	[sec]	[min]	[sec]	[min]	[sec]	[min]
Kubus	150	2,50	200	3,33	250	4,17
Tetrapod	200	3,33	250	4,17	300	5,00
Accropod	250	4,17	300	5,00	375	6,25

Hourly productions at 3.000 working seconds per hour:

Type	2,50 m3, 6 ton		5,00 m3, 12 ton		10,00 m3, 24 ton	
	[pcs/hr]	[pcs/hr]	[pcs/hr]	[pcs/hr]	[pcs/hr]	[pcs/hr]
Kubus	20,00		15,00		12,00	
Tetrapod	15,00		12,00		10,00	
Accropod	12,00		10,00		8,00	

Port of Rades: Armouring with Accropode I

ACCROPODE™ is a trademark of SOGREAH - France



ACCROPODE™ est une marque déposée par SOGREAH - France



ACCROPODE™

Shed Armouring Units (Limassol Marina)




Port of Zeebrugge: Sand retention breakwaters armoured with HARO's






**Remote-release handling
Hook detail**



CORE-LOC™ placing



Filter layer requirements: $W/15$ to $W/7$ (where W is the CORE-LOC™ unit weight)

Filter layer tolerances: $C/6$ (where C is the unit height)



**Single-layer
CORE-LOC™ armouring**



CORE-LOC® est une marque déposée par l'US Army Corps of Engineers USA



CORE-LOC® is a trademark of the US Army Corps of Engineers USA

CORE-LOC®

 **SOGEAH**
CONSULTANTS

Maritime & Dredging 2010

140

ACCROPODE™



ACCROPODE™ est une marque déposée par SOGREAH - France


ACCROPODE™ is a trademark of SOGREAH - France

ACCROPODE™



ACCROPODE™ is a trademark of SOGREAH - France

ACCROPODE™ est une marque déposée par SOGREAH - France



ACCROPODE™



ACCROPODE™ est une marque déposée par SOGREAH - France




ACCROPODE™ is a trademark of SOGREAH - France

Key Figures:

- 23 Mm³ of dredging
- 9 km of rubble-mound breakwaters
- 1,7 km floating breakwaters
- 2,2 km of super post-panamax quaywall

Jebel Ali New Container Terminal Phase 1



Jebel Ali New Container Terminal Extension



Construction of rock-bund and reclamation of container –terminal area

Jebel Ali New Container Terminal Extension



Container Port Jebel Ali, Dubai




Container Port Jebel Ali, Dubai

Armouring with 11 ton Stablit CAU's



Sea-defence works: sea-dikes




Sea-dike, Bredene (Belgium)



Coastal protection structures: groynes

JETÉE N°22 SUR LA PLAGE DE BLANKENBERGE
STRANDHOOFD Nr 22 · OP HET STRAND TE BLANKENBERGE
COUPE A-B. DOORSNEDE A-B.



Coastal groyne , Ostend (Belgium)



Groyne Fields, Cadzand



Concrete in Waterfront Engineering.


Challenges:

- **limited sustainability (> 100 years ?)**
- **sensitive to sulphate weathering (sea-water environment)**
- **reinforcement corrosion**
-

Concrete for Waterfront structures: High Sulfate Resisting (HSR) Concrete





- Granulates : 0/4, 4/16, 16/32 or 4/32: grades in mm ranges @ 750 l/m³
- Sand: Rhine-sand @ 400 l/m³
- water : water/cement factor = 0,4
- Low-Alkali Cement (either or not self-compacting):
 - Lean Concrete
 - C15 (ca 100 kg Cement/m³): workfloor, ...
 - C20 : blinding support
 - Rich Concrete
 - C30 : precasting
 - C40 (ca 400 kg Cement/m³)
- Cement- containing additives:
 - micro-silicates: to improve durability
 - fly-ash : as a (cheap) substitute for cement
 - colloids : to make concrete hydrophobic
- Additives to influence hardening:
 - Slow-down: when concrete-plant is remote
 - Accelerators: when formworks have to be removed swiftly
 - Mix e.g. Glenium (BASF): first slow-down, then accelerated
- Reinforcement:
 - fibre-glass (improves tensile strength)
 - steel with active cathodic protection
 - epoxy- coated steel
 - stainless steel

Compression Strength Tests on Concrete



Concrete Caissons for Breakwaters or Quaywalls





Dry-docks used for caisson-construction



Colloidal Concrete (info cfr Interbeton):

- **open structure**
- **closed structure**

Hydromix is een merknaam van Interbeton
Cfr www.heidelbergcement.com

Characteristics:


- UCS = 7 N/mm²
- $\rho = 1750 \text{ kg /m}^3$
- $k = 2 \cdot 10^{-4}$ to $2 \cdot 10^{-7} \text{ m/sec}$



Underwater Concrete with closed structure (cfr Hydromix)



Sheetpile Walls : U- orf Z- profiles



Choice of profile depends upon:

- Ultimate soil/water load (horizontal soil pressure): U-profile has a stronger bending moment, Z-profile is more economic
- Type of Soil :
 - Resistant Soils (e.g. $q_c > 2 \text{ MPa}$ or SPT > 15) with difficult driveability: U profile preferred (= stronger)
 - Soft soils with good driveability: Z-profile preferred because more cost-effective (relative to kg of steel)

Accelerated Low-water Corrosion in Oxygen-rich water environment (top part & splash zone):

Protection by:

- Overwidth on steel : corrosion = ca 0,10mm/year
- Coatings (epoxy) ...but risks of damage during driving
- Cathodic protection, either passive with sacrificial Zn-anodes (1kg/m² exposed), either active, with DC


Application of sheet-piles in cofferdams



Double sheet-pile wall, Blankenberge (Belgium)

Maritime & Dredging 2010

163




Combi-Walls:

Combination of deeper tubes (stability) with shallow U-profiled sheetpiles (soil/water retention)




Bouw van de 2^{de} Sluis te Evergem: Buispalen en Combi-walls



New lock-chamber at Evergem-Lock on Canal Ghent-Terneuzen






Combiwall in Danish Quay-Wall , Albert I dock, Zeebrugge, Belgium




Monitoring horizontal movements in Combi-Walls


Monitoring : inclinometers (3/4)




Construction of Albert II-Dok Quay-Wall (Zeebrugge)



Renovation of Quaywallss in the port of Ghent, Belgium



After Renovation



Sheetpiles in Waterfront Engineering: flexible, cheap, but...

Accelerated Low Water Corrosion (ALWC)

What ?

In the tidal range and splash zone and to ca 1 to 2m under the LW-line, bacteria are agglutinated to the steel causing an acid-corrosion: the result is a strongly accelerated corrosion and oxydation of the steel.

Normally, a corrosion of 0,08mm to 0,17 mm/year/wet surface is to be considered

ALWC corrodes up to 0,3mm to 2mm/year/wet surface !

Solutions?

Cathodic Protection with sacrificial (Zn) anodes

Epoxy-coatings

Calcium Carbonate/ Mg - hydroxyde coating


Concrete Tube-Piles or Steel Tube-Piles (fully or partially filled with (reinforced) concrete) for breasting Dolphins, Mooring Dolphins



Steel Tube-Piles: choice is determined by steel-quality, i.e. the Flow-limit of the steel.


Generally, it appears to be more cost-effective to use lighter tube-piles with a high-quality steel (instead of larger tube-piles, with lower steel-quality).

Dimensions are engineered via bending moments, driving depth (geotechnics,...),....




Massive gravity quay-walls

Existing quay-wall structure



After renovation , Port of Klaipeda, Lit




IMPACT RECONSTRUCTION



Maritime & Dredging 2010


176

Gravity Quaywalls, constituted of Concrete Blocks, Cove Canal, UAE



Examples of Engineered Block-Walls


CROSS SECTION A-A



Name	Class (c)	Time Δt (min/m)
Bedding Layer (100 mm)		100
Quarry Run	0.1-0.2	700
Gravel (50 mm)		700
Blinding Layer (10 mm)		200
Concrete Fill		400
Frost attack		700

Examples of Engineered Block-Walls , Cruise Terminal

DESIGN PARAMETERS QUAYWALL	
Surcharge	= 10kN/m ² (trucks)
Max. Water Difference	= 0.2m
F _{bollard}	= 1000kN
Sloping	= 1.5
Severing	= 1.5





Palm Cove Canal, UAE:

**More than 12 km of qua-wall constructed
with 25 to 32 ton unreinforced concrete
blocks**





Course-1: 4-side mould.



Overview Precast Yard



Course-1: casting 2-side mould



Overview Precast Yard



Mould C2



Lifting Course-2 block



Mould C3



Placing course-2 block.



Formwork Course-4B, Precast Front Panel. Casting position..



Course-4B "Precast Front Panel": Lifting block out of mould.



Formwork Course-4B, Precast Front Panel. Open position after removing block.



Course-4B "Precast Front Panel": Stockpile & GFRP-bars for connection with C4A.



Course-4B "Precast Front Panel": Placing blocks at Quay Wall.



Mould Course-4A



Course-4B "Precast Front Panel": Side view with mould Course-4A



Pontoon Corner



Return corner section-1



In-situ casted "Pontoon-Corner" after completion

Massive Gravity Wall cast in-situ: example of Verrebroeck-Dock, Port of Antwerp



Fixed Formwork in corners




Sliding formwork

Verrebroeck-Dock: Port of Antwerp





Controlled Inundation Area at Kruibeke Bazel Rupelmonde (KBR), River Scheldt: construction of dewatering sluices





KBR at LW



KBR at HW



KBR at extreme HW

Maritime & Dredging 2010

